

isc Silicon PNP Power Transistor
2SA2039
DESCRIPTION


- Large current capacitance
- High-speed switching
- 100% avalanche tested
- High allowable power dissipation
- Minimum Lot-to-Lot variations for robust device performance and reliable operation
- Complementary to 2SC5706
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- DC/DC converter, relay drivers, lamp drivers, motor drivers, flash

ABSOLUTE MAXIMUM RATINGS (T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CBO}	Collector-Base Voltage	-50	V
V _{CEO}	Collector-Emitter Voltage	-50	V
V _{EBO}	Emitter-Base Voltage	-6	V
I _C	Collector Current-Continuous	-5	A
I _{CM}	Collector Current-Peak	-7.5	A
P _C	Collector Power Dissipation @ T _C =25°C	15	W
	Collector Power Dissipation @ T _a =25°C	0.8	
T _J	Junction Temperature	150	°C
T _{stg}	Storage Temperature Range	-55~150	°C





isc Silicon PNP Power Transistor
2SA2039
ELECTRICAL CHARACTERISTICS

 T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage	I _C = -1.0A; I _B = -50mA			-0.195	V
V _{CE(sat)-2}	Collector-Emitter Saturation Voltage	I _C = -2.0A; I _B = -100mA			-0.43	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = -2.0A; I _B = -100mA			-1.2	V
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = -1mA; I _B = 0	-50			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = -10uA; I _C = 0	-6			V
I _{CBO}	Collector Cutoff Current	V _{CB} = -40V; I _E = 0			-1.0	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = -4V; I _C = 0			-1.0	μ A
h _{FE}	DC Current Gain	I _C = -0.5A; V _{CE} = -2V	200		560	
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = -10V; f= 1.0MHz		24		pF
f _T	Current-Gain—Bandwidth Product	I _C = -500mA; V _{CE} = -10V		360		MHz

Outline Drawing



NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.