


**isc Silicon NPN Power Transistor**
**2SC1004**
**DESCRIPTION**


- With TO-3 Package
- High breakdown voltage
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**

- for use in horizontal deflection output stages for color TV receives


**ABSOLUTE MAXIMUM RATINGS(T<sub>a</sub>=25°C)**

SYMBOL	PARAMETER	VALUE	UNIT
V <sub>CBO</sub>	Collector-Base Voltage	1100	V
V <sub>CEO</sub>	Collector-Emitter Voltage	700	V
V <sub>EBO</sub>	Emitter-Base Voltage	5	V
I <sub>C</sub>	Collector Current-Continuous	0.5	A
I <sub>B</sub>	Base Current-Continuous	0.1	A
P <sub>C</sub>	Collector Power Dissipation	50	W
T <sub>J</sub>	Junction Temperature	150	°C
T <sub>stg</sub>	Storage Temperature Range	-55~150	°C



## isc Silicon NPN Power Transistor

2SC1004

## ELECTRICAL CHARACTERISTICS

T<sub>c</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 150mA; I <sub>B</sub> = 30mA			5.0	V
V <sub>BE(sat)</sub>	Base-Emitter Saturation Voltage	I <sub>C</sub> = 150mA; I <sub>B</sub> = 30mA			1.5	V
V <sub>(BR)CEO</sub>	Collector-Emitter Breakdown Voltage	I <sub>C</sub> = 10mA; I <sub>B</sub> = 0	700			V
V <sub>(BR)EBO</sub>	Emitter-Base Breakdown Voltage	I <sub>E</sub> = 1mA; I <sub>C</sub> = 0	5			V
I <sub>CBO</sub>	Collector Cutoff Current	V <sub>CB</sub> = 800V; I <sub>E</sub> = 0			1	uA
I <sub>EBO</sub>	Emitter Cutoff Current	V <sub>EB</sub> = 4V; I <sub>C</sub> = 0			1	uA
h <sub>FE</sub>	DC Current Gain	I <sub>C</sub> = 0.15A; V <sub>CE</sub> = 15V	30		160	
f <sub>T</sub>	Current-Gain—Bandwidth Product	I <sub>C</sub> = 0.15A; V <sub>CE</sub> = 15V		2		MHz

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.